



Halogen HV



LED HV



Halogenfrei

Produkteigenschaften

Einbautiefe	100 mm
Außendurchmesser	68 mm
Auslassöffnung	66 mm
Klappenlänge	50 mm
Klappenbreite	26 mm
Rand Lampenöffnung	5 mm
Stärke Kappe	0,8 - 1,0 mm
Farbe	transparent

Geeignete Leuchten: Niedervoltleuchten mit max. 35W mit AL-Reflektor (keine Kaltlichtlampen)

Schutzkappe Hochvolt 230 V / LED - Für eine längere Haltbarkeit von Leuchtmitteln

- » Optimal geeignet für (Hochvolt) Halogeneinbaustrahler LED
- » Schützt LED vor Überhitzung
- » Einfacher und nachträglicher Einbau
- » Aktiver Brandschutz in Hohlwanddecken
- » Nicht geeignet für Kaltlichtlampen

Serie	-
Artikelnummer	9068-PRI
Kategorie	Brandschutz
Montageart	-
Einsatz	Deckenbeleuchtung
EAN	4260182060841

Materialeigenschaften

Material	Silikon-Kautschuk
----------	-------------------



Product features

Installation depth	100 mm
Outer diameter	68 mm
Outlet opening	60 mm
Flap length	50 mm
Flap width	26 mm
Edge lamp opening	5 mm
Thickness cap	0,8 - 1,0 mm
Color	transparent

Suitable luminaires: Low-voltage luminaires with max. 35W with AL reflector (no cold light lamps).

Protective cap high voltage 230 V / LED - For a longer shelf life of illuminants

- » Ideally suited for recessed halogen spotlights, LED
- » Easy retrofit installation
- » Protects LED from overheating
- » Active fire protection
- » Not suitable for cold light lamps

Series	-
Article No.	9068-PRI
Category	Fire protection
Type of installation	-
Use	ceiling lighting
EAN	4260182060841

Material properties

Material	Silicone-rubber
----------	-----------------