



Produkteigenschaften

|                                         |        |
|-----------------------------------------|--------|
| Durchmesser außen                       | 138 mm |
| Durchmesser innen                       | 135 mm |
| Sollbruchstelle Deckel für Tellerventil | 135 mm |
| Abstand Schraubdome für Tellerventil    | 102 mm |
| Höhe                                    | 90 mm  |
| Farbe                                   | orange |
| Durchmesser Sichtfläche                 | 155 mm |

Lüftungshülse - Bis zu 30 min Zeitersparnis pro Aussparung

- » Für Ortbeton oder Werksfertigung
- » Schraubdome für Lüftungsteller integriert
- » Direkter Anschluss genormter Lüftungen, Ø 125 mm
- » Mit oder ohne Magnetbefestigung
- » Keine Aussparung mehr basteln

|               |                          |
|---------------|--------------------------|
| Serie         | -                        |
| Artikelnummer | P827                     |
| Kategorie     | Betoninstallation        |
| Montageart    | Nagel, Kleber            |
| Einsatz       | Ortbeton, Werksfertigung |
| EAN           | 4260182064450            |

Materialeigenschaften

|          |    |
|----------|----|
| Material | PP |
|----------|----|

Mögliche Hersteller für Verwendung

|                                   |
|-----------------------------------|
| Helios Ventilatoren GmbH + Co KG  |
| Zehnder Group AG                  |
| Maico Elektroapparate-Fabrik GmbH |
| Kermi GmbH                        |
| Systemair GmbH                    |
| Wolf GmbH                         |



Product features

|                                                     |        |
|-----------------------------------------------------|--------|
| Diameter outside                                    | 138 mm |
| Diameter inside                                     | 135 mm |
| Predetermined breaking point cover for poppet valve | 135 mm |
| Distance screw domes for poppet valve               | 102 mm |
| Height                                              | 90 mm  |
| Color                                               | orange |
| Diameter of visible area                            | 155 mm |

Ventilation sleeve - Up to 30 min time saving per recess

- » For cast-in-place concrete or prefabrication
- » Screw domes for ventilation plates integrated
- » Direct connection of standardized vents, Ø 125 mm
- » With or without magnet fastening
- » No more tinkering with recesses

|                      |                                        |
|----------------------|----------------------------------------|
| Series               | -                                      |
| Article No.          | P827                                   |
| Category             | Concrete installation                  |
| Type of installation | Nail, glue                             |
| Use                  | cast-in-place concrete, prefabrication |
| EAN                  | 4260182064450                          |

Material properties

|          |    |
|----------|----|
| Material | PP |
|----------|----|

possible manufacturer for use

|                                   |
|-----------------------------------|
| Helios Ventilatoren GmbH + Co KG  |
| Zehnder Group AG                  |
| Maico Elektroapparate-Fabrik GmbH |
| Kermi GmbH                        |
| Systemair GmbH                    |
| Wolf GmbH                         |